

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	0	(blade with clearance) and turbine and ((inflatable with fluid with pump) same signal same pump same (control\$4 with pressure))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/18 12:47
L2	0	(blade with clearance) and turbine and (inflatable same fluid same signal same pump same (control\$4 with pressure))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/18 12:47
S1	769	(blade with tip with clearance with turbine)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/17 18:47
S3	50	S1 and stator and (shroud with segment)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/03 15:08
S4	0	S3 and actuator and (sens\$3 with turbin with parameter)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/03 16:39
S5	0	S3 and actuator and (sens\$3 with parameter)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/03 15:09
S6	5	S3 and actuator	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/03 16:38
S7	2	"5219268".pn.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/03 15:12

S8	0	S1 and actuator and (sens\$3 with turbin with parameter)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/03 15:12
S9	769	(blade with tip with clearance with turbine)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/03 16:38
S10	50	S9 and stator and (shroud with segment)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/17 17:12
S11	8	S10 and sensor	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/03 16:38
S12	4	S11 and actuator	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/03 16:45
S13	0	S12 and model	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/17 16:09
S14	0	S10 and model	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/03 16:45
S15	64	S9 and model	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/03 16:46

S16	0	S15 and ( model same (tip with clearance with prediction) same (turbin with parameter))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/03 16:47
S17	0	S15 and ( model same (tip with clearance with prediction))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/03 16:47
S18	0	S15 and ( model same (turbin with parameter))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/03 16:48
S19	26	S15 and (controller microprocessor processor)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/03 16:48
S20	4	S19 and (command with signal)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/16 17:57
S21	218	(control\$3 with blade with tip with clearance with turbine)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/03 17:18
S22	0	S21 and (turbin with parameter)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/03 17:19
S23	38	S21 and parameter	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/03 17:19

S24	1	S23 and (command with signal)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/03 17:19
S25	2	"702"/\$.cds. and (clearance with turbine) and controller and sensor and command	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/03 17:26
S26	0	702/145 and (clearance with turbine) and controller and sensor	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/03 17:27
S27	0	702/145 and (clearance with turbine)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/03 17:27
S28	0	(turbine with parameter) and (tip with clearance) and ((command with signal) same parameter same clearance)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/16 15:45
S29	0	(turbine with parameter) and (clearance with turbin) and ((command with signal) same parameter same clearance)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/16 15:45
S30	2	"5219268".pn.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/16 17:57
S31	0	S30 and (command with signal)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/16 17:58

S32	0	(command with signal) same (turbin with parameter) same (tip with clearance)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/16 18:03
S33	0	(command with signal) same (turbin with parameter)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/16 18:03
S34	0	(command with signal) same (turbine with parameter) same (tip with clearance)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/16 18:03
S35	76	(command with signal) same (turbine with parameter)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/16 18:03
S36	0	S35 and ((command with signal) same (tip with clearance))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/16 18:04
S37	0	S35 and ((command with signal) same (turbine with clearance))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/16 18:04
S38	771	(blade with tip with clearance with turbine)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/17 16:09
S39	50	S38 and stator and (shroud with segment)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/17 16:09

S40	8	S39 and sensor	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/17 16:09
S41	4	S40 and actuator	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/17 16:09
S42	4	S41 and control\$4	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/17 17:11
S43	771	(blade with tip with clearance with turbine)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/17 17:16
S44	133	S43 and (shroud with segment)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/17 17:12
S45	6	S44 and sensor and actuator	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/17 17:13
S46	0	S45 and (sensor with parameter)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/17 17:14
S47	0	S45 and (sensor with pressure)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/17 17:14

S48	0	S45 and (sensor with temperature)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/17 17:14
S49	0	S44 and (sensor with parameter)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/17 17:14
S50	0	(blade with tip with clearance) and turbine and (shroud with segment) and (sens\$3 with parameter) and (controller microprocessor)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/17 17:19
S51	0	(blade with tip with clearance) and (turbine with parameter) and (shroud with segment) and (controller microprocessor)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/17 17:19
S59	2	(blade with tip with clearance) and turbine and (actuator with around with shroud)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/17 18:57
S60	2	(blade with clearance) and turbine and (actuator with around with shroud)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/18 10:27
S61	2	clearance and turbine and (actuator with around with shroud)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/17 18:58
S62	11	turbine and (actuator with around with shroud)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/17 19:07

S63	16	turbine and ((actuators with shroud) same (tip with blade))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/17 19:08
S66	7	(blade with clearance) and turbine and (casing with shroud with actuator)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/02/18 12:45